We can line anything. Kynar® PVDF Liner



Kynar® PVDF liners from Witt are a flexible version of Kynar sheeting. Witt Kynar liners are 100% PVDF, not a PVDF coated fabric. Our Kynar liners offer the flexibility to be fabricated into a drop-in liner while maintaining tremendous resistance to a wide range of aggressive chemicals. The material also carries with it extremely high purity and high abrasion resistance.

SPECIFICATIONS

PROPERTIES	TYPICAL VALUES	STANDARDS
Hardness	50-60 Shore D	ASTM D-2240
Specific Gravity	1.80—1.82	ASTM D-792
Tensile Yield Strength	1700—2800 PSI	ASTM D-638
Tensile Break Strength	2000-4500	ASTM D-638
Tensile Break Elongation	500-800 %	ASTM D-638
Flexural Strength	1500-2500 PSI	ASTM D-790
Flexural Modulus	28000-40000 PSI	ASTM D-790
Compressive Strength	2,000 - 3,000 PSI	ASTM D-695
Operating Temp.	0°F - 190°F	

These datum, which are believed to be reliable, are published for information use only as it is rarely possible to duplicate actual operating conditions in laboratory testing. Consequently, no guarantee, explicit or implied, is given that similar results will be obtained in actual operating conditions.

Witt Lining Systems... the best choice for you!

- 45+ years of commitment to industrial lining solutions
- Dedicated to industrial liners only
 no ponds, lagoons, pools, etc.
- Innovative product ideas and fabrication techniques
- Honored by US Dept. of Commerce



© 2018 Witt Lining Systems



witt lining systems
We can line anything.

www.wittliners.com

800.323.3335 | P.O. Box 488 | Claremore, OK 74018