

We can line anything.

High Performance Koroseal® PVC Liner



PRODUCT FEATURES:

- Proprietary compound formulations that build upon the long-term success of standard Koroseal® Linings with enhancements that result in significantly reduced plasticizer mobility and the associated extraction rates.
- Designed to provide enhanced protection and performance in the harshest corrosive environments.
- Improved tolerance to process/chemistry anomalies that can cause periodic elevated temperature excursions.
- Infrequent process temperature excursions to 215°F can be tolerated without causing measurable plasticizer migration and the resultant reduction in service life.
- Reduced plasticizer mobility results in longer service life and the associated reduction in overall life cycle cost of ownership.
- Process tank liners can be expected to provide improved reliability and up-time.

Property	Typical Performance	Test Method
Hardness	91 ± 5	ASTM D-2240
Tensile	2500 psi	ASTM D-412
Ultimate Elongation	200%	ASTM D-412
Specific Gravity	1.2353	ASTM D-792
Color	Black	Visual

These datum, which are believed to be reliable, are published for information use only as it is rarely possible to duplicate actual operating conditions in laboratory testing. Consequently, no guarantee, explicit or implied, is given that similar results will be obtained in actual operating conditions.

Witt Lining Systems... the best choice for you!

- 45+ years of commitment to industrial lining solutions
- Dedicated to industrial liners only – no ponds, lagoons, pools, etc.
- Innovative product ideas and fabrication techniques
- Honored by US Dept. of Commerce



witt lining systems

We can line anything.

www.wittliners.com

800.323.3335 | P.O. Box 488 | Claremore, OK 74018

© 2017 Witt Lining Systems